

E-Dome 300

1



Technical Data

Floor Area:	3046 sq ft
Diameter	62 ft
Ceiling Height	31 ft
Volume	63390 cubic ft

Membrane options

Transparent front (1): White, opaque PVC membrane with detachable, exchangeable clear, transparent front part, our most versatile solution
Blackout (2): White, opaque PVC membrane with detachable, exchangeable white, opaque front part, ideal for darkening out the interior
Transparent membrane (3): Completely transparent PVC cover, ideal for night events, giving you the possibility to create magical light effects
Branded membrane (4): Fully color printed membrane or printed detachable front part, ideal to put your brand's message across
Open dome (5): unique 2-in-1 solution that combines the classic dome shape with a completely innovative mobile stage system
* Opaque PVC membranes can be replaced with non-opaque, single layer cover, perfect for creative lighting effects visible from the outside

Membrane material specification

Surface area:	570 m ² (total) / 53 m ² (front part only)
Membrane material:	PVC Coated Polyester Fabrics
Thickness:	650 g/m ² (non-opaque) 800 g/m ² (opaque)
Certifications:	Class B1 and M2 of fire resistance according to DIN 4102

Steel framework

Structure material	Steel S235JR
Structure finish	Hot-dip, double sided galvanized, powder coated white (other RAL colors available)
Strut details	555 struts / 35 mm diameter / 2.5 mm strut's wall thickness
Strut length	1728 min. - 2057 max.
Connecting bolts	M16 zinc-coated bolts
Structure feet number	30


Entrances / Doors / Openings

Number of entrances	2 (up to 3 optionally)
Width of circular entrance	5 ft (at floor level) / 11 ft (at the center)
Height of circular entrance	8 ft
Membrane door:	3x PVC membrane zip door (white or transparent)
Aluminum-glass door:	Optional double wing aluminum-glass door with anti-panic system and safe glass.
Aluminum-glass door entrance dimensions:	Height: 7 ft / Width: 5 ft
Ventilation	5 ventilation openings at the top AC / Heating opening available on request
Windows	Circular or triangular transparent membrane windows available on request

Membrane options



Dimensions



Safety

Windloads	0.5 (dynamic pressure q = kN/m ²)
Dynamic pressure	11 Beaufort / violent storm
Extra load allowed	1674 - 2810 lbs (suspended load)
Extra load points	Min.: 16 / Max.: 50

Load parameters

Steel framework	4739 lbs / 2x 2.1 x 0.7 x 0.9 m
Membrane	992 lbs / 2x 1.5 x 1.3 x 0.5 m

Assembly / Dismantle

Assembly time	12 hours / 8-10 persons crew
Dismantle time	7 hours / 10 persons crew
Equipment required	40t crane

All sizes, weights and volumes listed in this table are rounded approximations and may deviate due to varying materials or production processes.

All the information in this table refers to our standard configuration and materials. Please contact us if you have queries about dome customization (material types & colors, interconnected structures, flooring, interior accessories, air conditioning, branding, etc.)

Euphoria Event Solutions

102 Skitchewaug St.

Windsor, CT 06095

860.547.0773

info@euphoriaevents.com

www.euphoriaevents.com